

## What mode does the MM850 optical module have



### Overview

The eSFP-GE-SX-MM850 optical module is a Huawei Gigabit multimode optical module with DOM/DDM support, which is packaged in an SFP package with a center wavelength of 850 nm. When used with multimode optical fiber (LC/PC-LC/PC OM2), the transmission distance can reach up to 550 m, the transmission. Want to learn more?

Looking for something else?

This H3C® SFP-GE-SX-MM850-A compatible SFP transceiver provides 1000Base-SX throughput up to 550m over multi-mode fiber (MMF) using a wavelength of 850nm via an LC connector. It is guaranteed to be 100% compatible with the equivalent H3C® transceiver. Designed for extended temperatures (-40°C to 85°C), it includes Digital Optical Monitoring (DOM) and. This H3C SFP-GE-SX-MM850-A optics is a high performance and cost-effective small form factor pluggable transceiver. No power injector is provided with the AP. See "Connecting the AP to the power source" for the.

## Article Content

H3C SFP-GE-SX-MM850-A MANUAL Pdf Download | ManualsLib

Installing the AP IMPORTANT: To ensure radio coverage, have the AP installed by technical personnel as a best practice. When you install the AP, follow these restrictions and guidelines: • The AP is large ...

H3C SFP-GE-SX-MM850-A Datasheet

This H3C SFP-GE-SX-MM850-A optics is a high performance and cost-effective small form factor pluggable transceiver. It is suitable for 1000BASE-SX Gigabit Ethernet and 1G Fibre Channel ...

XG-SFP-SR-MM850 10GBASE-SR SFP+ 850-nm 300-m DOM Duplex LC MMF Optical ...

The XG-SFP-SR-MM850 is aligned to IEEE 10GBASE-SR optical specifications and supports a link length of up to 300 m (984.25 ft., with OM3 optical cables) or 400 m (1312.34 ft., with OM4 optical ...

SFP-GE-SX-MM850-IN

Home Products Transmission Switches Optical Modules SFP-GE-SX-MM850-IN Gigabit Multi-Mode 500m Optical Module Specification

H3C SFP-XG-SX-MM850-E 10GBASE-SR SFP+ Module, Multi-Mode ...

It supports multi-mode fiber with a reach of 300m via a duplex LC connector. Designed for extended temperatures (-40°C to 85°C), it includes Digital Optical Monitoring (DOM) and guarantees full ...

H3C SFP-XG-SX-MM850-E 10GBASE-SR SFP

It supports multi-mode fiber with a reach of 300m via a duplex LC connector. Designed for extended temperatures (-40°C to 85°C), it includes Digital Optical ...

SFP-GE-SX-MM850-IN 1.25G Multi-Mode 550m SFP Optical ...

025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved. \*Product specifications and availability are subject to change without notice. \*Despite our best efforts, technical or typographical errors may ...

SFP-GE-SX-MM850

Overview 1. Gigabit Ethernet 2. Fiber Channel 3. Switch to Switch interface 4. Switched backplane applications 5. Router/Server interface 6. Other optical transmission systems

Huawei eSFP-GE-SX-MM850 Gigabit Optical Module Overview

The eSFP-GE-SX-MM850 optical module is a Huawei Gigabit multimode optical module with DOM/DDM support, which is packaged in an SFP package with a center wavelength of 850 nm. ...

#### Sfp-ge-sx-mm850-a-c Datasheet

This H3C® SFP-GE-SX-MM850-A compatible SFP transceiver provides 1000Base-SX throughput up to 550m over multi-mode fiber (MMF) using a wavelength of 850nm via an LC connector.

#### Support

You can choose optical modules as needed for data transmission over optical fibers. The optical modules include optical transmitters, optical receivers, transceivers, and transponders.

#### XG-SFP-SR-MM850 10GBASE-SR SFP+ 850-nm 300-m DOM ...

The XG-SFP-SR-MM850 is aligned to IEEE 10GBASE-SR optical specifications and supports a link length of up to 300 m (984.25 ft., with OM3 optical cables) or 400 m (1312.34 ft., with OM4 optical ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.automationauthoritiesolar.co.za>

Email: [info@automationauthoritiesolar.co.za](mailto:info@automationauthoritiesolar.co.za)

Phone: +27 82 547 3961

Address: 15 Quantum Street, Technopark, Centurion, 0157, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

